

Features

- 1210 size
- Magnetic shielding
- High Q characteristic
- High current rating
- RoHS compliant*

CMH322522 Series - Shielded Wirewound Chip Inductor

Electrical Specifications

Inductance				Test	SRF	DCR	Irms
Bourns			Q	Freq. MHz	MHz	Ω	mA
Part No.	μH	Tol. %	Min.	L,Q	Min.	Max.	Max.
CMH322522-R10ML	0.10	±20	30	100	700	0.44	450
CMH322522-R12ML	0.12	±20	30	25.2	500	0.22	450
CMH322522-R15ML	0.15	±20	30	25.2	450	0.25	450
CMH322522-R18ML	0.18	±20	30	25.2	400	0.25	450
CMH322522-R22ML	0.22	±20	30	25.2	350	0.32	450
CMH322522-R27ML	0.27	±20	30	25.2	320	0.36	450
CMH322522-R33ML	0.33	±20	30	25.2	300	0.40	450
CMH322522-R39ML	0.39	±20	30	25.2	250	0.45	450
CMH322522-R47ML	0.47	±20	30	25.2	220	0.50	450
CMH322522-R56ML	0.56	±20	30	25.2	180	0.55	450
CMH322522-R68ML	0.68	±20	30	25.2	160	0.60	450
CMH322522-R82ML	0.82	±20	30	25.2	140	0.65	450
CMH322522-1R0KL	1.0	±10	30	7.96	120	0.70	400
CMH322522-1R2KL	1.2	±10	30	7.96	100	0.75	390
CMH322522-1R5KL	1.5	±10	30	7.96	85	0.85	370
CMH322522-1R8KL	1.8	±10	30	7.96	80	0.90	350
CMH322522-2R2KL	2.2	±10	30	7.96	75	1.0	320
CMH322522-2R7KL	2.7	±10	30	7.96	70	1.1	290
CMH322522-3R3KL	3.3	±10	30	7.96	55	1.2	260
CMH322522-3R9KL	3.9	±10	30	7.96	50	1.3	250
CMH322522-4R7KL	4.7	±10	30	7.96	45	1.5	220
CMH322522-5R6KL	5.6	±10	30	7.96	40	1.6	200
CMH322522-6R8KL	6.8	±10	30	7.96	35	1.8	180
CMH322522-8R2KL	8.2	±10	30	7.96	30	2.0	170
CMH322522-100KL	10	±10	30	2.52	28	2.1	150
CMH322522-120KL	12	±10	30	2.52	20	2.5	140
CMH322522-150KL	15	±10	30	2.52	20	2.8	130
CMH322522-180KL	18	±10	30	2.52	20	3.3	120
CMH322522-220KL	22	±10	30	2.52	19	3.7	110
CMH322522-270KL	27	±10	30	2.52	18	5.0	80
CMH322522-330KL	33	±10	30	2.52	16	5.6	70
CMH322522-390KL	39	±10	30	2.52	15	6.4	65
CMH322522-470KL	47	±10	30	2.52	13	7.0	60
CMH322522-560KL	56	±10	30	2.52	12	8.0	55
CMH322522-680KL	68	±10	30	2.52	11	9.0	50
CMH322522-820KL	82	±10	30	2.52	10	10	45
CMH322522-101KL	100	±10	20	0.796	9	10	40

General Specifications

Temperature Rise

......20 °C max. at rated current

Operating Temperature

-55 °C to +125 °C

Storage Temperature

.....-55 °C to +125 °C Reflow Soldering .. 230 °C, 50 sec. max.


Resistance to Soldering Heat

......260 °C, 5 seconds


Materials

Core Ferrite
Terminal Electrode Cu/Sn
Packaging 2,000 pcs. per reel

Product Dimensions



Recommended Layout



DIMENSIONS: $\frac{MM}{(INCHES)}$




WARNING Cancer and Reproductive Harm - www.P65Warnings.ca.gov


Applications

 Prevention of electromagnetic interference to signals on the secondary side of electronic equipment

CMH322522 Series - Shielded Wirewound Chip Inductor **BOURNS**

Packaging Specifications





DIMENSIONS: $\frac{MM}{(INCHES)}$

BOURNS®

Asia-Pacific: Tel: +886-2 2562-4117 • Email: asiacus@bourns.com

EMEA: Tel: +36 88 520 390 • Email: eurocus@bourns.com

The Americas: Tel: +1-951 781-5500 • Email: americus@bourns.com

www.bourns.com

REV. 01/16

Specifications are subject to change without notice.

Users should verify actual device performance in their specific applications.

The products described herein and this document are subject to specific legal disclaimers as set forth on the last page of this document, and at www.bourns.com/docs/legal/disclaimer.pdf

Legal Disclaimer Notice



This legal disclaimer applies to purchasers and users of Bourns® products manufactured by or on behalf of Bourns, Inc. and its affiliates (collectively, "Bourns").

Unless otherwise expressly indicated in writing, Bourns® products and data sheets relating thereto are subject to change without notice. Users should check for and obtain the latest relevant information and verify that such information is current and complete before placing orders for Bourns® products.

The characteristics and parameters of a Bourns® product set forth in its data sheet are based on laboratory conditions, and statements regarding the suitability of products for certain types of applications are based on Bourns' knowledge of typical requirements in generic applications. The characteristics and parameters of a Bourns® product in a user application may vary from the data sheet characteristics and parameters due to (i) the combination of the Bourns® product with other components in the user's application, or (ii) the environment of the user application itself. The characteristics and parameters of a Bourns® product also can and do vary in different applications and actual performance may vary over time. Users should always verify the actual performance of the Bourns® product in their specific devices and applications, and make their own independent judgments regarding the amount of additional test margin to design into their device or application to compensate for differences between laboratory and real world conditions.

Unless Bourns has explicitly designated an individual Bourns® product as meeting the requirements of a particular industry standard (e.g., ISO/TS 16949) or a particular qualification (e.g., UL listed or recognized), Bourns is not responsible for any failure of an individual Bourns® product to meet the requirements of such industry standard or particular qualification. Users of Bourns® products are responsible for ensuring compliance with safety-related requirements and standards applicable to their devices or applications.

Bourns® products are not recommended, authorized or intended for use in nuclear, lifesaving, life-critical or life-sustaining applications, nor in any other applications where failure or malfunction may result in personal injury, death, or severe property or environmental damage. Unless expressly and specifically approved in writing by two authorized Bourns representatives on a case-by-case basis, use of any Bourns® products in such unauthorized applications might not be safe and thus is at the user's sole risk. Life-critical applications include devices identified by the U.S. Food and Drug Administration as Class III devices and generally equivalent classifications outside of the United States.

Bourns expressly identifies those Bourns® standard products that are suitable for use in automotive applications on such products' data sheets in the section entitled "Applications." Unless expressly and specifically approved in writing by two authorized Bourns representatives on a case-by-case basis, use of any other Bourns® standard products in an automotive application might not be safe and thus is not recommended, authorized or intended and is at the user's sole risk. If Bourns expressly identifies a sub-category of automotive application in the data sheet for its standard products (such as infotainment or lighting), such identification means that Bourns has reviewed its standard product and has determined that if such Bourns® standard product is considered for potential use in automotive applications, it should only be used in such sub-category of automotive applications. Any reference to Bourns® standard product in the data sheet as compliant with the AEC-Q standard or "automotive grade" does not by itself mean that Bourns has approved such product for use in an automotive application.

Bourns® standard products are not tested to comply with United States Federal Aviation Administration standards generally or any other generally equivalent governmental organization standard applicable to products designed or manufactured for use in aircraft or space applications. Bourns expressly identifies Bourns® standard products that are suitable for use in aircraft or space applications on such products' data sheets in the section entitled "Applications." Unless expressly and specifically approved in writing by two authorized Bourns representatives on a case-by-case basis, use of any other Bourns® standard product in an aircraft or space application might not be safe and thus is not recommended, authorized or intended and is at the user's sole risk.

The use and level of testing applicable to Bourns® custom products shall be negotiated on a case-by-case basis by Bourns and the user for which such Bourns® custom products are specially designed. Absent a written agreement between Bourns and the user regarding the use and level of such testing, the above provisions applicable to Bourns® standard products shall also apply to such Bourns® custom products.

Users shall not sell, transfer, export or re-export any Bourns® products or technology for use in activities which involve the design, development, production, use or stockpiling of nuclear, chemical or biological weapons or missiles, nor shall they use Bourns® products or technology in any facility which engages in activities relating to such devices. The foregoing restrictions apply to all uses and applications that violate national or international prohibitions, including embargos or international regulations. Further, Bourns® products and Bourns technology and technical data may not under any circumstance be exported or re-exported to countries subject to international sanctions or embargoes. Bourns® products may not, without prior authorization from Bourns and/or the U.S. Government, be resold, transferred, or re-exported to any party not eligible to receive U.S. commodities, software, and technical data.

To the maximum extent permitted by applicable law, Bourns disclaims (i) any and all liability for special, punitive, consequential, incidental or indirect damages or lost revenues or lost profits, and (ii) any and all implied warranties, including implied warranties of fitness for particular purpose, non-infringement and merchantability.

For your convenience, copies of this Legal Disclaimer Notice with German, Spanish, Japanese, Traditional Chinese and Simplified Chinese bilingual versions are available at:

Web Page: http://www.bourns.com/legal/disclaimers-terms-and-policies

PDF: http://www.bourns.com/docs/Legal/disclaimer.pdf

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Bourns:

CMH322522-100KL CMH322522-2R2KL CMH322522-270KL CMH322522-680KL CMH322522-820KL

CMH322522-101KL CMH322522-120KL CMH322522-150KL CMH322522-180KL CMH322522-1R0KL CMH322522
1R2KL CMH322522-1R5KL CMH322522-1R8KL CMH322522-220KL CMH322522-2R7KL CMH322522-330KL

CMH322522-390KL CMH322522-3R3KL CMH322522-3R9KL CMH322522-470KL CMH322522-4R7KL CMH322522
560KL CMH322522-5R6KL CMH322522-6R8KL CMH322522-8R2KL