

e-MMC also provides a high-speed memory card interface compliant with JEDEC Version 5.0/5.1, eliminating the need for users to be concerned about directly controlling NAND flash memories. Thus, e-MMC can easily be used as a storage device for embedded applications.

Product list of e-MMC

Capacity	Part Number	Class	e-MMC Version	Max Data Rate (MB/s)	Supply Voltage		Operating Temperature (°C)	Package	
					V <sub>CC</sub> (V)	V <sub>CCQ</sub> (V)		Size (mm)	Code
4GB	THGBMNG5D1LBAIT	Consumer	5.0	400	2.7 to 3.6	1.70 to 1.95, 2.7 to 3.6	-25 to 85	11×10×0.8	P-WFBGA153-1110-0.50
	THGBMNG5D1LBAIL	Consumer	5.0	400	2.7 to 3.6	1.70 to 1.95, 2.7 to 3.6	-25 to 85	11.5×13×0.8	P-WFBGA153-1113-0.50
8GB	THGBMJG6C1LBAIL	Consumer	5.1	400	2.7 to 3.6	1.70 to 1.95, 2.7 to 3.6	-25 to 85	11.5×13×0.8	P-WFBGA153-1113-0.50
	THGBMJG6C1LBAU7	Industrial	5.1	400	2.7 to 3.6	1.70 to 1.95, 2.7 to 3.6	-40 to 105 <sup>(1)</sup>	11.5×13×1.0	P-VFBGA153-1113-0.50
16GB	THGBMJG7C1LBAIL	Consumer	5.1	400	2.7 to 3.6	1.70 to 1.95, 2.7 to 3.6	-25 to 85	11.5×13×0.8	P-WFBGA153-1113-0.50
	THGAMRG7T13BAIL *	Consumer	5.1	400	2.7 to 3.6	1.70 to 1.95	-25 to 85	11.5×13×0.8	P-WFBGA153-1113-0.50
	THGBMJG7C2LBAU8	Industrial	5.1	400	2.7 to 3.6	1.70 to 1.95, 2.7 to 3.6	-40 to 105 <sup>(1)</sup>	11.5×13×1.2	P-TFBGA153-1113-0.50
32GB	THGBMJG8C2LBAIL	Consumer	5.1	400	2.7 to 3.6	1.70 to 1.95, 2.7 to 3.6	-25 to 85	11.5×13×0.8	P-WFBGA153-1113-0.50
	THGAMRG8T13BAIL *	Consumer	5.1	400	2.7 to 3.6	1.70 to 1.95	-25 to 85	11.5×13×0.8	P-WFBGA153-1113-0.50
	THGBMJG8C4LBAU8	Industrial	5.1	400	2.7 to 3.6	1.70 to 1.95, 2.7 to 3.6	-40 to 105 <sup>(1)</sup>	11.5×13×1.2	P-TFBGA153-1113-0.50
64GB	THGAMRG9T23BAIL *	Consumer	5.1	400	2.7 to 3.6	1.70 to 1.95	-25 to 85	11.5×13×0.8	P-WFBGA153-1113-0.50



[Memory](#) | [SSD](#) | [Where to Buy](#) | [News](#)

128GB	THGAMRT0T43BAIR *	Consumer	5.1	400	2.7 to 3.6	1.70 to 1.95	-25 to 85	11.5×13×1.0	P-VFBGA153-1113-0.50
-------	-------------------	----------	-----	-----	------------	--------------	-----------	-------------	----------------------

- Note (1) : Tc=115°C max.
- \* New Product : Contact the KIOXIA Corporation's sales representative for sample schedule about new products.
- Details about your intended usage would be checked before submitting samples of the Industrial class product.

Links

MLC/NAND Flash Memory

- [e-MMC](#)
- [UFS](#)
- [e-MMC/UFS for Automotive Information & Entertainment Systems](#)

 [Open in new window.](#)  [Open PDF in new window.](#)

[Business](#) > [Memory](#) > [NAND Flash Memories with an Integrated Controller](#) > [e-MMC](#)

**Home**

**About**

[About Us](#)  
[News](#)

**Business**

[Memory](#)  
[SSD](#)  
[Where to Buy](#)  
[News](#)

**Personal**

[News](#)

**KIOXIA Global site**  
**(KIOXIA Holdings Corporati**

[About Us](#)  
[Sustainability](#)  
[Product & Technology](#)  
[News](#)



# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Kioxia:](#)

[THGBMJG8C4LBAU8](#)