




TACTILE SWITCHES



Active

PRODUCT DRAWING
English

3D PDF

TE CONNECTIVITY (TE)

FSMRA2JH04=R/A,TACT PB SW,160G

Alcoswitch | FSMRAJ

1825027-5

TE Internal Number: 1825027-5

Alias ID: FSMRA2JH

Always EU RoHS/ELV Compliant

Actuator Style **Round**

Operating Function **No**

Contact Base Material **Copper Alloy**

Contact Plating **Silver**

Dust Proof **No**

Product Drawings

MICRO-MINIATURE PUSHBUTTON SWITCH

PDF
English

CAD Files

Customer View Model

3D_IGS.ZIP
English

Customer View Model

3D_STP.ZIP
English

Customer View Model

2D_DXF.ZIP
English

3D PDF

PDF
English

Catalog Pages/Data Sheets

SWITCHES_CORE_PROGRAM_CATALOG

PDF
English

Product Environmental Compliance

TE Material Declaration

MD_1825027-5_08012012621

PDF
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features

Actuator Style **Round**

Dust Proof **No**

Leg Style **Vertical**

Leg Style	Rinked
Illuminated	With
Product Type	Switch

Configuration Features	Operating Function	No
	Support Bracket	With
	Configuration (Pole-Throw)	Single Pole - Single Throw
	Number of Actuators	1
	ESD Grounding Terminal	Without
	Ganged	With
	Tactile	Yes
	Snap Action	Without
	Tactile Feel	With

Body Features	Actuator Color	Black
	Bushing Style	Unthreaded
	Actuator Material	PBT
	Actuator Force	160 g [5.648 oz]
	Actuator Profile	Extended
	Case Color	Black
	Body Style	Right Angle
	Case Material	Nylon

Contact Features	Contact Base Material	Copper Alloy
	Contact Plating	Silver
	Contact Current Rating (mA)	50

Termination Features	Termination Type	Printed Circuit Board
----------------------	------------------	------------------------------

Mechanical Attachment	Mounting Type	Through Hole
	Mounting Angle	With

Housing Features	Low Profile	With
	Process Sealed	No

Dimensions	Actuator Length	1.24 mm [.049 in]
	Switch Height	7 mm [.276 in]

Button Width

3.5 mm [.138 in]

Usage Conditions

Temperature Rating (°C)

Standard

Packaging Features

Packaging Method

Loose Piece

Other

Comment





(On) indicates momentary position.

Product Compliance

[Statement of Compliance](#)
PDF

[VIEW ALL PRODUCT COMPLIANCE](#)

CUSTOMERS ALSO BOUGHT

CRIMP RINGS & SPADES	THROUGH-HOLE RESISTORS	USB CONNECTORS	RECTANGULAR POWER CONNECTORS
			
TERMINAL, PIDG PVF2 R, 16-14, 6 53415-1	LR0204 1% 240K LR0204F240K	RECP ASSY, R/A, 4P, THRU- HOLE, USB, LF 6364372-2	02P MINI UMNL HDR ASSY AU LF 1-770872-1
Save to List Find Similar Products	Save to List Find Similar Products	Save to List Find Similar Products	Save to List Find Similar Products