PART NUMBER BUTTON COLOR ED903 RED ED913 BLACK BUTTON COLOR SEE TABLE SEE TABLE SEE TABLE NOTES: I. MATERIALS: PUSHBUTTON - THERMOPLASTIC. SEE TABLE FOR COLOR SECTION A-A SW TCH HOUSING & ADAPTER - BRASS, NUCKEL PLATED SECTION A-A SW TCH HOUSING S - STAINLESS STELL SECTION A-A SW TCH SPRING - STAINLESS STELL UP TO Ø0.30 FLEX RELIFF - THERMOPLASTIC RUBBER, BLACK CLAMP PLATES - STAINLESS STELL FLEX RELIFF - STRAMESS STELL 0.12 FLEX RELIFF - STRAMESS COMPLIANT. 0.12 A CONTINUE Q.31 Q.31 Q.34				\downarrow	7	
ED913 BLACK BUTTON COLOR SEE TABLE PUSHBUTTON - THERMOPLASTIC, SEE TABLE FOR COLOR SWITCH HOUSING & ADAPTER - BRASS, NICKEL PLATED SWITCH TERMINALS - BRASS, SILVER PLATED SWITCH TERMINALS - BRASS, SILVER PLATED SWITCH INSULATORS - PHENOLIC HANDLE - ZINC ALLOY, NICKEL PLATED SWITCH INSULATORS - PHENOLIC HANDLE - STAINLESS STEEL FLEX RELIEF - THERMOPLASTIC RUBBER, BLACK CLAMP PLATES - STAINLESS STEEL FLEX RELIEF - SCREWS - STEEL, NICKEL PLATED 2. THESE PRODUCTS ARE ROHS COMPLIANT. 0.12 Ø 0.31 Ø 0.31 Ø 0.31 Ø 0.34 Ø 0.31	PART NUM	JER BUTTON	I COLOR			
NOTES: I. MATERIALS: PUSHBUTTON - THERMOPLASTIC, SEE TABLE FOR COLOR SWITCH HOUSING & ADAPTER - BRASS, NICKEL PLATED SWITCH TERMINALS - BRASS, SILVER PLATED SWITCH TRUNINGS - PHENDLIC HANDLE - ZINC ALLOY, NICKEL PLATED FLEX RELIEF - STRAINLESS STEEL FLEX RELIEF SCREWS - STEEL, NICKEL PLATED 2. THESE PRODUCTS ARE ROHS COMPLIANT. A O C O B O C O C O C O C O C O C O C O C	E D 9 O 3	R	E D			and a starter
SEE TABLE NOTES: 1. MATERIALS: PUSHBUTTON - THERMOPLASTIC, SEE TABLE FOR COLOR SWITCH HOUSING & ADAPTER - BRASS, NICKEL PLATED SWITCH SPRING - STAINLESS STEEL SWITCH SPRING - STAINLESS STEEL SWITCH INSULATORS - PHENOLIC HANDLE - ZINC ALLOY, NICKEL PLATED FLEX RELIEF - THERMOPLASTIC RUBBER, BLACK CLAMP PLATES - STAINLESS STEEL FLEX RELIEF SCHWS - STEEL, NICKEL PLATED 2. THESE PRODUCTS ARE ROHS COMPLIANT. A O O O O O O O O O O O O O O O O O O O	ED9I3	BL	ACK			
1. MATERIALS: PUSHBUTTON - THERMOPLASTIC, SEE TABLE FOR COLOR SWITCH HOUSING & ADAPTER - BRASS, NICKEL PLATED SWITCH TERMINALS - BRASS, SILVER PLATED SWITCH TREMINALS - STAINLESS STEEL SWITCH INSULATORS - PHENOLIC HANDLE - ZINC ALLOY, NICKEL PLATED FLEX RELIEF - THERMOPLASTIC RUBBER, BLACK CLAMP PLATES - STAINLESS STEEL FLEX RELIEF SCREWS - STEEL, NICKEL PLATED 2. THESE PRODUCTS ARE ROHS COMPLIANT. A O B O C B O C C B O C C C C C C C C C C C C C						
PUSHBUTTON - THERMOPLASTIC, SEE TABLE FOR COLOR SWITCH HOUSING & ADAPTER - BRASS, NICKEL PLATED SWITCH SERVING - STAINLESS STEEL SWITCH INSULATORS - PHENOLIC HANDLE - ZINC ALLOY, NICKEL PLATED FLEX RELIEF - THERMOPLASTIC RUBBER, BLACK CLAMP PLATES - STAINLESS STEEL FLEX RELIEF SCREWS - STEEL, NICKEL PLATED 2. THESE PRODUCTS ARE ROHS COMPLIANT. A C C C C C C C C C C C C C C C C C C	NOTES:					
FLEX RELIEF - THERMOPLASTIC RUBBER, BLACK CLAMP PLATES - STAINLESS STEEL FLEX RELIEF SCREWS - STEEL, NICKEL PLATED 2. THESE PRODUCTS ARE ROHS COMPLIANT. A O C O B O C O B O C O C O C O C O C O C O C O C	PUSHBUT SWITCH SWITCH SWITCH SWITCH	TON - THERMOP HOUSING & ADA TERMINALS - B SPRING - STAI INSULATORS -	APTER - BR BRASS, SIL INLESS STE PHENOLIC	RASS, NICKEL PLATED LVER PLATED EEL	SECTION A-A	ACCEPTS CABLE
A \bigcirc	FLEX REI CLAMP PI FLEX REI	LIEF - THERMO LATES - STAIN LIEF SCREWS -	DPLASTIC R NLESS STEE - STEEL, N	RUBBER, BLACK EL NICKEL PLATED	3.00	
	А О— С О— В О—	SCHEMATIC		Ø 0.31	Switchcraft	
				STAR SYMBOL DENOTES CRITICAL DIMENSION		
DI SWITCHCHAPTING, AND IS RELEASED ON A CONFIDENTIAL DASIS FOR IDENTIFICATION FORFOSES ONLY.				UNLESS OTHERWISE SPECIFIED	SIZE WIDTH MULT	LBS/M TEMPER
UNLESS OTHERWISE SPECIFIED SIZE WIDTH MULT LBS/M TEMPER				I. ALL DIMENSIONS IN INCHES -TWO PLACE DECIMALS ±0.01	FINISH	MATERIAL
UNLESS OTHERWISE SPECIFIED SIZE WIDTH MULT LBS/M TEMPER				-THREE PLACE DECIMALS ± 0.005	SPEC No.	SPEC No.
Image: Second						
Image: Second state UNLESS OTHERWISE SPECIFIED SIZE WIDTH MULT LBS/M TEMPER Image: Second state Image: Second state Image: Second state SIZE WIDTH MULT LBS/M TEMPER Image: Second state Image: Second state Image: Second state Image: Second state SiZE WIDTH MULT LBS/M TEMPER Image: Second state Image: Second state Image: Second state Image: Second state Second state Second state Second state Image: Second state Image: Second state Image: Second state Image: Second state Second state Second state Image: Second state Image: Second state Image: Second state Image: Second state Second state Image: Second state Image: Second state Image: Second state Image: Second state Second state Image: Second state Image: Second state Image: Second state Image: Second state Second state				-ALL DIA. CONCENTRIC WITHIN 0.005 T.I.R.	1:1	
Image: Construction Image: Construct			T IV T IK	-ALL DIA. CONCENTRIC WITHIN 0.005 T.I.R. 2. FEATURES ON THE SAME CENTERLINE MUST BE ALIGNED WITHIN ±0.002	I:I DATE DRAWN BY CHKD APVD LL Manuelo WD JS RV	
Image: Constraint of the state of the s				-ALL DIA. CONCENTRIC WITHIN 0.005 T.I.R. 2. FEATURES ON THE SAME CENTERLINE MUST BE ALIGNED WITHIN ±0.002 K 3. REMOVE ALL BURRS	I:I DATE DRAWN BY CHKD APVD II-May-IO WR JS RV II-28-78 II-28-78 II-28-78	78 SHEET OF
Image: Construction Image: Construct	REV ECO NU	JMBER DATE		-ALL DIA. CONCENTRIC WITHIN 0.005 T.I.R. 2. FEATURES ON THE SAME CENTERLINE MUST BE ALIGNED WITHIN ±0.002 K 3. REMOVE ALL BURRS	Ι:Ι DATE DRAWN BY CHKD APVD II-May-IO WR JS RV NAME II-28-78 II-28-78	78 SHEET OF PART No. REV

Pro/Engineer CAD File

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Switchcraft: ED903 ED913