





Rev	AWO #	Description	Date	Appr
-		RELEASED	11/16/04	

APPROVED: _____
DATE: _____ TITLE: _____



SPECIFICATION:

Material:
Insulator: PBT, rated UL-94V-0
Contacts: Brass
Contact Plating:
Gold Flash over Nickel underplate overall
Electrical:
Operating Voltage: 250V AC max.
Current rating: 3 Amps max.
Contact resistance: 20 mohms max
Insulation resistance: 5000 Mohms min
Dielectric withstanding voltage: 1000 VAC / minute
Mechanical:
Mating durability: 500 cycles min.
Temperature Rating:
Operating temperature: -55° TO +105°
Environmental:
Lead free, RoHS compliant.



A = .100 [2.54] X No. of Positions / 2 + .300 [7.60]
B = .100 [2.54] X No. of Positions / 2 + .200 [5.08]
C = .100 [2.54] X No. of Spaces

UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE INCHES [MM] TOLERANCES: EXCEPT AS NOTED		ADAM TECH 909 Rahway Avenue, Union, NJ 07083 Phone: 908-687-5000 Fax: 908-687-5710	
INCHES HOLES			
.X ± .10	∅X ± .10	TITLE BOX HEADER, VERTICAL PCB MOUNT, 2 ROW .100 PITCH, GOLD FLASH PLATED	
.XX ± .020	∅XX ± .015		
.XXX ± .015	∅XXX ± .010	REV. -	
APPROVALS		DATE	
DRAWN	SS	11/16/04	
CHECKED		SIZE X	PART NO. BHR-XX-VUA
APPROVED		REF:	SCALE: NTS SHEET 1 OF 1