

Item no.: 257-862
 Product description: MODULAR PCB TERMINAL BLOCK 2 SOLDER PINS / POLE
 1 POLE PIN SPACING 10/10.16 MM / 0.4 IN ANGLED LEVER



Produkt kann von Bild abweichen / product may differ

Packing unit 300 3*100 pieces

RoHS compliant

Product group	4 (Printed Circuit)
Weight	1.618 g
Color	dark gray
No. of connection Points	1
No. of potentials	1
pole count	1
Height	20.2 mm
Height	0.795 in
Width	10 mm
Width	0.394 in
Depth	14.2 mm
Depth	0.559 in
Pin spacing from	10 mm
Pin spacing up to	10.16 mm
Pin spacing from	0.394 in
Pin spacing up to	0.4 in
Pollution degree	2
Measured voltage EN	1000 V
Measured shock voltage	8 kV

Current intensity EN
Pollution degree
Measured voltage EN

24 A
2
1000 V



Measured shock voltage	8 kV
Current intensity EN	24 A
Connection method	CAGE CLAMP® CONNECTION
Cross section [mm ²]	0.08 - 2.5 mm ²
Wiring method	solid
Cross section [mm ²]	0.08 - 2.5 mm ²
Cross section [mm ²]	0.25 - 1.5 mm ²
Cross section [mm ²]	0.25 - 1.5 mm ²
Cross section [AWG]	28 - 12 AWG
Strip length from	5 mm
Strip length to	6 mm
Material group	I



Item no.	Admission office	Approval no.	Voltage [V]	Current [A]	Cross section [mm ²]
257-862	ABS	04-HG469925/1-PDA	1000/500	16	0,5-2,5
257-862	BV	11915/A0	1000/500	16	0,08-2,5
257-862	CCA	NL6250	500	24	0,08-2,5
257-862	DNV	E-9215	1000/500	16	0,08-2,5
257-862	GL	17296-00HH	1000/500	16	0,5-2,5
257-862	KEMA	2110204.04	500	24	0,08-2,5
257-862	RMR	11130002	500	16	0,5-2,5
257-862	UR	E45172	300	15	28-12

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected