



# Chip Multilayer Hybrid Baluns



LDB18 Series

\*Terminal of "NC" should be fixed to the no connected pattern.  
 All the technical data and Information contained herein are subject to change without prior notice.



LDB21 Series

\* Terminal of "NC" should be connected to the floating land.  
 \* All the technical data and information contained herein are subject to change without prior notice.

Part Number	Frequency Range (MHz)	Insertion Loss I) (dB)	Insertion Loss II) (dB)	Unbalance Impedance (Nom.) (ohm)	Balance Impedance (Nom.) (ohm)	Application
LDB181G8115G-120	1810 ±100MHz	1.1 max. (at 25°C)	1.2 max. (-40~+85°C)	50	150	GSM
LDB181G8120G-120	1810 ±100MHz	1.2 max. (at 25°C)	1.3 max. (-40~+85°C)	50	200	GSM
LDB181G9505C-110	1955.0 ±35.0MHz	1.2 max. (at 25°C)	1.3 max. (-40~+85°C)	50	50	GSM
LDB181G9510C-110	1955.0 ±35.0MHz	1.2 max. (at 25°C)	1.3 max. (-40~+85°C)	50	100	GSM
LDB182G4505C-110	2450.0 ±50.0MHz	1.0 max. (at 25°C)	1.1 max. (-40~+85°C)	50	50	WLAN/BT
LDB182G4510C-110	2450.0 ±50.0MHz	1.0 max. (at 25°C)	1.1 max. (-40~+85°C)	50	100	WLAN/BT
LDB182G4510G-120	2450.0 ±50.0MHz	1.1 max. (at 25°C)	1.2 max. (-40~+85°C)	50	100	WLAN/BT
LDB182G4520C-110	2450.0 ±50.0MHz	1.3 max. (at 25°C)	1.4 max. (-40~+85°C)	50	200	WLAN/BT
LDB182G5005G-120	2500 ±200MHz	1.15 max. (at 25°C)	1.25 max. (-40~+85°C)	50	50	WIMAX
LDB182G5010G-120	2500 ±200MHz	1.1 max. (at 25°C)	1.2 max. (-40~+85°C)	50	100	WIMAX
LDB183G4505G-120	3450 ±150MHz	1.25 max. (at 25°C)	1.35 max. (-40~+85°C)	50	50	WIMAX
LDB183G4510G-120	3450 ±150MHz	1.25 max. (at 25°C)	1.35 max. (-40~+85°C)	50	100	WIMAX
LDB183G6005G-120	3600 ±300MHz	1.3 max. (at 25°C)	1.4 max. (-40~+85°C)	50	50	WIMAX
LDB183G6010G-120	3600 ±300MHz	1.4 max. (at 25°C)	1.5 max. (-40~+85°C)	50	100	WIMAX
LDB183G7010C-110	3700.0 ±300.0MHz	1.4 max. (at 25°C)	1.5 max. (-40~+85°C)	50	100	GSM
LDB184G5010C-110	4500.0 ±300.0MHz	1.1 max. (at 25°C)	1.2 max. (-40~+85°C)	50	100	GSM
LDB185G3705G-120	5375 ±475MHz	1.50 max. (at 25°C)	1.65 max. (-40~+85°C)	50	50	WLAN/BT
LDB185G3710G-120	5375 ±475MHz	1.20 max. (at 25°C)	1.35 max. (-40~+85°C)	50	100	WLAN/BT
LDB18869M10G-120	869.5 ±45.5MHz	1.0 max. (at 25°C)	1.1 max. (-40~+85°C)	50	100	GSM
LDB18869M15G-120	869.5 ±45.5MHz	1.0 max. (at 25°C)	1.1 max. (-40~+85°C)	50	150	GSM
LDB211G8105C-001	1815 ±105MHz	1.0 max. (at 25°C)	1.1 max. (-40~+85°C)	50	50	GSM
LDB211G8110C-001	1810 ±100MHz	0.8 max. (at 25°C)	0.9 max. (-40~+85°C)	50	100	GSM
LDB211G8115C-001	1810 ±100MHz	0.8 max. (at 25°C)	0.9 max. (-40~+85°C)	50	150	GSM
LDB211G8120C-002	1810 ±100MHz	0.8 max. (at 25°C)	0.9 max. (-40~+85°C)	50	200	GSM
LDB212G4005C-001	2400 ±100MHz	0.8 max. (at 25°C)	0.9 max. (-40~+85°C)	50	50	WLAN/BT
LDB212G4010C-001	2400 ±100MHz	0.9 max. (at 25°C)	1.0 max. (-40~+85°C)	50	100	WLAN/BT
LDB212G4020C-001	2400 ±100MHz	0.95 max. (at 25°C)	1.05 max. (-40~+85°C)	50	200	WLAN/BT
LDB213G7010C-002	3700 ±300MHz	1.0 max. (at 25°C)	1.1 max. (-40~+85°C)	50	100	GSM
LDB213G7020C-001	3700 ±300MHz	2.2 max. (at 25°C)	2.3 max. (-40~+85°C)	50	200	GSM
LDB215G1210C-001	5125 ±225MHz	1.10 max. (at 25°C)	1.25 max. (-40~+85°C)	50	100	WLAN/BT
LDB215G2505C-001	5250 ±100MHz	1.10 max. (at 25°C)	1.25 max. (-40~+85°C)	50	50	WLAN/BT
LDB215G2510C-001	5250 ±100MHz	0.95 max. (at 25°C)	1.10 max. (-40~+85°C)	50	100	WLAN/BT
LDB215G2520C-001	5250 ±100MHz	1.10 max. (at 25°C)	1.25 max. (-40~+85°C)	50	200	WLAN/BT
LDB215G3710C-001	5375 ±475MHz	0.95 max. (at 25°C)	1.10 max. (-40~+85°C)	50	100	WLAN/BT
LDB215G5105C-001	5512 ±363MHz	1.10 max. (at 25°C)	1.25 max. (-40~+85°C)	50	50	WLAN/BT
LDB215G5110C-001	5512 ±363MHz	0.95 max. (at 25°C)	1.10 max. (-40~+85°C)	50	100	WLAN/BT
LDB215G5120C-001	5512 ±363MHz	1.10 max. (at 25°C)	1.25 max. (-40~+85°C)	50	200	WLAN/BT
LDB21869M10C-001	869.5 ±45.5MHz	1.0 max. (at 25°C)	1.1 max. (-40~+85°C)	50	100	GSM
LDB21869M15C-001	869.5 ±45.5MHz	1.2 max. (at 25°C)	1.3 max. (-40~+85°C)	50	150	GSM
LDB21869M20C-001	869.5 ±45.5MHz	1.2 max. (at 25°C)	1.3 max. (-40~+85°C)	50	200	GSM

Continued on the following page.

Continued from the preceding page.

Part Number	Frequency Range (MHz)	Insertion Loss I) (dB)	Insertion Loss II) (dB)	Unbalance Impedance (Nom.) (ohm)	Balance Impedance (Nom.) (ohm)	Application
<b>LDB21881M05C-001</b>	881.5 ±12.5MHz	1.4 max. (at 25°C)	1.5 max. (-40~+85°C)	50	50	GSM
<b>LDB21881M20C-001</b>	881.5 ±12.5MHz	1.4 max. (at 25°C)	1.5 max. (-40~+85°C)	50	200	GSM
<b>LDB21942M05C-001</b>	942.5 ±17.5MHz	1.4 max. (at 25°C)	1.5 max. (-40~+85°C)	50	50	GSM
<b>LDB21942M20C-001</b>	942.5 ±17.5MHz	1.3 max. (at 25°C)	1.4 max. (-40~+85°C)	50	200	GSM
<b>LDM181G9310CC001</b>	1932.5 ±222.5MHz	0.85 max. (at 25°C)	0.95 max. (-40~+85°C)	50	100	UMTS
<b>LDM181G9610TA007</b>	1960 ±30MHz	0.55 max. (at 25°C)	0.60 max. (-40~+85°C)	50	100	UMTS
<b>LDM182G4505CC001</b>	2450 ±50MHz	0.88 max. (at 25°C)	0.98 max. (-40~+85°C)	50	50	WLAN/BT
<b>LDM182G4505GC004</b>	2450 ±50MHz	0.88 max. (at 25°C)	0.98 max. (-40~+85°C)	50	50	WLAN/BT
<b>LDM182G4510CC001</b>	2450 ±50MHz	0.75 max. (at 25°C)	0.85 max. (-40~+85°C)	50	100	WLAN/BT
<b>LDM182G4510HC003</b>	2450 ±50MHz	0.75 max. (at 25°C)	0.85 max. (-40~+85°C)	50	100	WLAN/BT
<b>LDM182G5005CC001</b>	2500 ±200MHz	0.9 max. (at 25°C)	1.0 max. (-40~+85°C)	50	50	WLAN/BT
<b>LDM185G4210CC001</b>	5425 ±525MHz	0.9 max. (at 25°C)	1.00 max. (-40~+85°C)	50	100	WLAN

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

## Murata:

[LDB21924M05C-001](#) [LDB181G8405C-110](#) [LDB21942M05C-001](#) [LDB21946M05C-002](#) [LDB31900M10C-437](#)  
[LDB31900M20C-416](#) [LDB213G7010C-002](#) [LDB182G4510C-110](#) [LDB213G6010C-001](#) [LDB21906M20C-001](#)  
[LDB32920M05D-463](#) [LDB312G4010C-418](#) [LDB32900M20C-200](#) [LDB32900M10C-200](#) [LDB212G1020C-001](#)  
[LDB212G1010C-001](#) [LDB212G4020C-001](#) [LDB212G4010C-001](#) [LDB21897M20C-001](#) [LDB312G4005C-300](#)  
[LDB32850M05C-200](#) [LDB211G9005C-001](#) [LDB211G8005C-001](#) [LDB311G2505E-423](#) [LDB212G4005C-001](#)  
[LDB43461M05C-400](#) [LDB21881M20C-001](#) [LDB21836M15C-002](#) [LDB215G3710C-001](#) [LDB211G7010C-001](#)  
[LDB182G4520C-110](#) [LDB185G3710G-120](#) [LDB211G6610C-002](#) [LDB211G6010C-001](#) [LDB211G6020C-001](#)  
[LDB43461M20C-400](#) [LDB211G8120C-002](#) [LDB311G9010C-440](#) [LDB211G8010C-001](#) [LDB211G8020C-001](#)  
[LDB311G5020C-420](#) [LDB211G4020C-001](#) [LDB211G3610C-001](#) [LDB211G7020C-001](#) [LDB211G5020C-001](#)  
[LDB211G5010C-001](#) [LDB311G8010C-451](#) [LDB32800M10C-200](#) [LDB311G8020C-409](#) [LDB211G9020C-001](#)  
[LDB211G9010C-001](#) [LDB21881M05C-001](#) [LDB311G8020C-300](#) [LDB212G5005C-001](#) [LDB311G6010C-300](#)  
[LDB311G6020C-300](#) [LDB212G1505C-001](#) [LDB212G1405C-001](#) [LDB212G1005C-001](#) [LDB215G5110C-001](#)  
[LDB215G5120C-001](#) [LDB311G5010C-300](#) [LDB311G9020C-300](#) [LDB311G7020C-300](#) [LDB311G7010C-300](#)  
[LDB215G2510C-001](#) [LDB21942M20C-001](#) [LDB21942M10C-001](#) [LDB21897M15C-003](#) [LDB21897M05C-001](#)  
[LDB183G7010C-110](#) [LDB211G7005C-001](#) [LDB21924M20C-001](#) [LDB211G5005C-001](#) [LDB213G6505C-001](#)  
[LDB21906M05C-001](#) [LDB21836M20C-001](#) [LDB312G4020C-301](#) [LDB213G7205C-001](#) [LDB211G6005C-001](#)  
[LDB31900M05C-417](#) [LDB184G5010C-110](#) [LDB311G5005C-300](#) [LDB311G9005C-300](#) [LDB311G7005C-300](#)  
[LDB311G6005C-300](#) [LDB311G8005C-300](#) [LDB181G9505C-110](#) [LDB181G9510C-110](#) [LDB182G4505C-110](#)  
[LDB181G8115G120](#) [LDB181G8120G120](#) [LDB182G4510G120](#) [LDB182G5005G120](#) [LDB182G5010G120](#)  
[LDB183G4505G-120](#) [LDB183G4510G-120](#) [LDB183G6005G120](#) [LDB183G6010G120](#) [LDB185G3705G120](#)